

BRVEN2

Indoor conventional call point



Technical data

Model	BRVEN2
Product code	PCPMC0101200
Activation	Manual alarm generated by pressing the centre of the recoverable front glass
Viewings	Local alarm red LED visible only after the glass pressure
Connections	Terminals
Connections possibility	With 880Ohm resistance in series or with the C – NO – NC contacts, connection terminals of the front LED
Internal selection	Jumper for 4400hm resistance selection in alternative to the 8800hm default resistance
Operating temperature	From -10 to 55°C – 93% U.R.
Protection class	Indoor IP2XD
Dimensions	W90 x H90 x D60mm W93,5 x H93,5 x D63,5 mm with transparent cover
Weight	175g
Power supply	DC24V of control unit line
Power consumption	50mA max limited from control unit line
Certification	Certified CPR 305/2011 (ex CPD 89/106/EEC certification) EN54-11
Parts supplied	Opening and reset wrench, screws and plugs, pigtails, technical manual

Key features

- Call point for TACÓRA conventional fire detection control units
- Manual alarm generated by pressing the center of the recoverable front glass
- IP2XD protection class (indoor)
- Dimensions W 90 x H90 x D60 mm
- Case opening and reset key provided
- Power supply DC24V
- Certified CPR 305/2011 (ex CPD 89/106/EEC certification) EN54-11