SPCK420.100 LCD keypad.2x16 Char.

Acre intrusion Standard Keypad

Acre intrusion LCD keypad with 2 x 16 character

Acre`s SPCK420/SPCK421 keypad provides a simple intuitive interface to the acre intrusion system.

Key Features

- **Powerful menu structure**
  The 2 line LCD display, soft keys, and multi-dimensional navigation key are ideal to operate smaller systems or single areas in a user-friendly way. Cause and effect integration
- **Integrated Card reader (SPCK421 only)**
  Can be used for authorisation without code for ease of access or with code for higher security.
- **Wireless expansion card option**
  The optional wireless module adds a wireless access point for wireless detectors and remote controls to allow excellent reception quality in the keypad area.
- **Easy configuration**
  Can be configured from the keypad or acre intrusion Web interface.

Keypad operations

- Full Engineer menus
- Users menus
- System Status
- Mapping gate control
- Add/Edit/Delete Users
- SMS setup
- View logs
- Multi Language
- Door control

SPCK420.100 LCD keypad.2x16 Char.

Acre intrusion Standard Keypad

Technical Data

Functional	
LED Indicators	3 status LEDs
Radio module	Optional (SPCW112)
Special keys	2 soft keys, 1 multi-dimensional navigation key

Intrusion	
Interfaces	X-BUS (in, out)

Power and mechanical	
Dimensions (W x H x D)	148 x 85 x 33 mm
Housing	Plastic housing (ABS)
Operating current	Max. 90 mA at 12 VDC (backlight, LEDs, sounder operated)
Operating temperature	5° ~ +40 °C
Operating voltage	9.5 ~ 14 VDC
Quiescent current	Max. 45 mA at 12 VDC
Tamper contact	Front / back spring tamper

General	
Colour	RAL 9003 (signal white)
LCD Display	2 x 16 characters
Mounting	Flat surface, wall-mounted
Weight	0.210 kg

SPCK420.100 LCD keypad.2x16 Char.

Acre intrusion Standard Keypad

Ordering Data

Type	Art. No.	Description	Weight*
Keypad	V54543-F101-A100	SPCK420	0.250 kg
Keypad	V54543-F101-A100	SPCK421	0.250 kg

* Total weight of the product inclusive of the weight of its accessories and packaging.