



Vanderbilt's WSIR-INT provides audible and visual indication of an alarm. Vanderbilt's WSIR-INT seamlessly blends style and security resulting in a class leading product. The WSIR-INT is slim and stylish and can be installed in seconds.

This device is easy to mount, easy to pair, and easy to configure, ensuring installation time is minimized. In addition, both devices use enhanced, low current RF technology which provides superior communications and ensures long battery life.

Key features

- Wall tamper protection
- EN Grade 2 approved
- Audible & visual indication
- Selectable output volume, 4 levels

Features & Benefits

- **Long battery life**

With high performance Lithium batteries and APS (Automatic Power Save) technology the WSIR-INT detectors have a battery life of 5 years.

- **Easy to pair**

Smart pairing mechanism allows the device to pair with the SPC transceiver in seconds.

Key features include:

- Automatic pairing on battery insertion
- LED guided Enrolment
- Unique serial number for each device

- **Long RF range**

Up to 500m transmission range in open space means that a single transceiver can cover the majority of installations.

- **Easy to configure**

The WSIR-INT device is entirely firmware configurable 'over the air'.

Configurable features include:

- Output control for audible and visual outputs
- Adjustable supervision time
- Full output control from SPC

- **Easy to mount**

The WSIR-INT can be mounted in seconds, the mounting plate is screwed to the target surface and the WSIR-INT clips into the plate.

Technical Data

Power and mechanical

Automatic power saving	Yes
Battery type	WSIR-INT: 2 x 1.5v Energizer AA Lithium batteries
Dimensions (W x H x D)	93 x 93 x 31 (mm)
Tamper contact	Front cover and removal
Transmit power	~ 14dBm

Intrusion

Event transmission	Alarm, Tamper, Supervision, Low battery
Supervision time	Selectable, 7 min by default

Connectivity

IP	IP41/IK04
----	-----------

General

Audio outputs	100dB at 1m
Battery life	5 Years
Current consumption	Standby ~60µA Receive mode ~26mA Transmit mode ~50 mA
E Vision (Compatibility)	8 lm at source
Range	500m transmission range in open space
Sound level	100dB at 1m
Weight	150g Nett

Ordering Data

Type	Art. No.	Description
WSIR-INT	V54538-F115-A100	WSIR-INT Wireless internal siren